Electronic Theodolite ZI 8009

Standards:

Specification:

The ZI 8009 Theodolites have Smart appearance, reasonable structure, practical functions. They are easy-to-use, and with excellent performance and reliable quality. (Includes: theodolite, tribrach, NiH rechargeable battery, Charger, user manual, and one year manufacturer warranty)

Specification: Telescope:

Magnification: 30XObjective Lens: 45mmOverall Length: 157mm

Stadia Ration: 100Stadia Constant: 0Image: Erectï€;

Field of View: 1° 30"Minimum Focus: 1.4mResolving Power: 3.0'

Electronic Angle Measurement:

- Reading System Photoelectric detection by incremental encoder
- Diameter of Circle (Vhz): 79mm
- Minimum Reading: 1"/5" (Selectable)

• Accuracy: 2"

Horizontal Angle: DualVertical Angle: Dual



Display:

 (LCD) Display Type: 2 sides, segment LCD in two lines

Level Sensitivity:

Plate Level: 30"/2mm (30" per 2mm)

• Circular Level: 8'/2mm (8" per 2mm)

Auto Vertical Compensator:

System: Liquid-electric detection/plate level selectable

• Working range: +3'

 Accuracy: 1" (Liquid-electric detection) 30""/2mm (plate level)

Optical Plummet Telescope:

• Image: Erect

• Magnification: 3X

• Focusing Range: 0.5m - infinity