



**ZEAL INTERNATIONAL** (An ISO 9001 Certified Company)

**Head Office:** 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

**Branch Office:** 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

**Warehouse:** 4/26 Kirti Nagar Industrial Area New Delhi - 110015

[info@zealinternational.com](mailto:info@zealinternational.com)

[sales@zealinternational.com](mailto:sales@zealinternational.com)

[support@zealinternational.com](mailto:support@zealinternational.com)

[quotation@zealinternational.com](mailto:quotation@zealinternational.com)

Visit us at: [www.zealinternational.com](http://www.zealinternational.com)

## Direct Shear (Motorised Twelve Speed) ZI 3055

Standards: IS 2720 (PART XIII)

Specification:

The apparatus comprises of the following.

### **Loading Unit:**

Supplied with load yoke with direct and lever system for applying load. Normal stress capacity 8 kg/sq. cm. Load is applied either directly or through a counter balanced detachable lever. Provision is made for the load to be applied either through a steel ball recessed in the loading pad or direct through a boss on the pre calibrated loading yoke. The loading unit is provided with V strips and roller strips for frictionless movement of shear box housing.

### **Shear Box Assembly:**

Comprising direct shear box in two halves for a square specimen size 60 x 60 x 25mm one pair of plain gripper plates, One pair of perforated gripper plates, one pair of porous stones, one top of loading pad.

### **Shear Box Housing:**

Accommodates the direct shear box assembly.

Complete with two ball roller strips.

Specimen cutter: for cutting 60 x 60 x 25 mm.

Specimen form larger samples. Set of weights to give a normal stress of 3kg/sa.cm. Through larger as following :

To give kg/cm. sq.	Qty.
0.05	4 nos.
0.1	1 no.



0.2	1 no.
0.5	3 nos.
1.0	1 no.

Complete set as above but without proving ring.  
Net weight 140 kg.

**Essential Accessories:**

High sensitivity compression proving ring. Cap 200kg. One consolidation dial gauge 0.01mm x 25mm and one strain dial gauge 0.01mm x 25mm

**Optional Extras:**

Additional set of weights to give a normal stress of 5 kg/cm<sup>2</sup>. Soil sampler for 60mm x 60mm specimen and test forms pad of 50.

**Spares:**

Porous stone for 60mm x 60mm size sample available in pairs.

Unit is electrically operated to give the following 12 rates or strains. 1.25, 0.625, 0.25, 0.125, 0.05, 0.025, 0.01, 0.005, 0.002, 0.001, 0.004 and 0.0002 mm/min. The apparatus is suitable for operation on 230 Volts Single Phase A.C. Supply.