



ZEAL INTERNATIONAL (An ISO 9001 Certified Company)

Head Office: 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

Branch Office: 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

Warehouse: 4/26 Kirti Nagar Industrial Area New Delhi – 110015

info@zealinternational.com

sales@zealinternational.com

support@zealinternational.com

quotation@zealinternational.com

Visit us at: www.zealinternational.com

Digital Double Door Drying Oven ZI 9014

Standards:

Specification:

This range of ovens is designed for drying large quantities of soil and aggregate samples and maintains temperature in accordance with most B.S. and ASTM requirements.

The 225 Lts. and 425 Lts. are economy models constructed with coated mild steel exterior and Stainless Steel coated interior chamber, which is both durable and corrosion resistant. These units meet the requirements of BS 1377 and are ideal for on-site laboratories and general soil and aggregate testing.

Options And Accessories:

- Dial thermometer with collar fixing for door
- Heavy duty shelves (on Request at an extra price)
- Color of the Oven (Only on qty. greater than 3 Units)

Specifications:

- The larger soil drying ovens are constructed with mild steel and powder coated exterior and Stainless Steel coated chamber which is both durable and corrosion resistant.
- All Sizes of Oven are fitted with a (PID Controller) having a microprocessor digital control as standard.
- All units comes with MCB tripping device in



cases of any short circuit, overloading of voltage and Low voltage cut off. Wiring of heaters can be connected / dis-connected removing the side panels of the Oven.

- Caster wheels with locking arrangement are fitted below the Oven for easy movability of the unit from one place to another. Door locking arrangement is very easy & convenient with lever to lock & unlock with half turn lever
- A Safety Thermostat is fitted inside the Oven for safety purpose. Incase of the failure of the PID controller the safety thermostat will serve as the temperature controller.
- A High / Low switch is fitted on the panel of the Oven for Heaters. This feature allows heaters to burn all together or half of them.
- The Least Count Division for viewing / setting the Temperature is 0.1° C

Technical Specifications:

Model No.	Capacity (litres)	Temperature	Fluctuation	No. of Shelves	No. shelf positions	Weight (kg)
ZI 9014-225	225	Ambient-200° C	0.75	3	4	90
ZI 9014-425	425	Ambient-200° C	0.75	4	5	170
ZI 9014-750	750	Ambient-200° C	0.5	5	8	200
ZI 9014-1000	1000	Ambient-200° C	0.5	5	11	240