



**ZEAL INTERNATIONAL** (An ISO 9001 Certified Company)

**Head Office:** 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

**Branch Office:** 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

**Warehouse:** 4/26 Kirti Nagar Industrial Area New Delhi - 110015

[info@zealinternational.com](mailto:info@zealinternational.com)

[sales@zealinternational.com](mailto:sales@zealinternational.com)

[support@zealinternational.com](mailto:support@zealinternational.com)

[quotation@zealinternational.com](mailto:quotation@zealinternational.com)

Visit us at: [www.zealinternational.com](http://www.zealinternational.com)

## Digital Manometer JPI 1006

Standards:

Specification:

**Accuracy:** 20 to 30°C (68 to 86°F): 0.1% rdg + 0.1% FS + 1 digit

-10 to 50°C (14 to 122°F): 0.15% rdg + 0.15% FS + 1 digit

**Operating Temp.:** -10 to 50°C (15 to 120°F)

**Compatible Media:** Dry, non-corrosive gases

**Power:** 2 AA batteries included (approx. 200 hours operation)

**Auto-off:** Selectable

**Zero Adjustment:** autozero

**Display:** 4-digit, 0.5" (12.7 mm), backlight with low battery indication

**Pressure Units:** mbar, bar, psi, Pa, kPa, inH<sub>2</sub>O, inHg, mmH<sub>2</sub>O, mH<sub>2</sub>O, mm/cm/mHg

**Pressure Port:** Tube fitting for 0.155" < ID > 0.195"; OD < 0.24" Tygon or silicon tubing (not included)

**Dimensions:** 155 H X 67 W X 40 mm D (6.1 x 2.6 x 1.6")

**Weight:** 180 g (6.4 oz)

