



ZEAL INTERNATIONAL (An ISO 9001 Certified Company)

Head Office: 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

Branch Office: 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

Warehouse: 4/26 Kirti Nagar Industrial Area New Delhi – 110015

info@zealinternational.com

sales@zealinternational.com

support@zealinternational.com

quotation@zealinternational.com

Visit us at: www.zealinternational.com

Humidity Indicator JPI 10015

Standards:

Specification:



Display

2 Digits 7 Segment LEDs 0.56" character height
(For Humidity)

3 Digits 7 Segment LEDs 0.56" character height
(For Temp.)

Resolution

1% For Relative Humidity & 0.1°C for Temperature

Range

0 to 99% Humidity and 0 to 99.9°C temperature

Accuracy

$\pm 2\%$ for RH ± 1 Least Significant Digit. $\pm 0.2^\circ\text{C}$ for
Temperature ± 1 Least Significant Digit.

Sensors

2 Nos. PT100 in sealed stainless steel tubing

Power

230V AC \pm 15%

Sensor Body

Casted Aluminum body with built-in water container facility to connect a water 'drip' also

Water Wick

Made of pure cotton. To be used with preferably, distilled water, & slight air breeze

Size

96 mm Panel Mounting Cut-Out 92 x 92 mm

Weigh

1.2 Kg (including sensor)